

Specification

ALTH0770A



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Design concept

Innovative modular design, the lamp in the form of a whole module can be fixed to the installation base through the form of permanent magnet, before installation can be very easy to adjust the Angle, and then installed on. The design of the lamp is also very characteristic, after the installation is completed, the whole lamp is similar to suspended on the ceiling, making the single ceiling more embellished.

Range of application


Hotels, supermarkets, office space, home lighting, commercial chains, etc.



ALTH0770A-7W


Basic parameter

Warranty	5 years
Wattage	7W
Size(mm)	Φ85*H86
Cutout	Φ75
Installation	embedded
IP Rating	IP20
Beam Angle	15°23°38°
Fitting Material	Aluminum
Finish Color	Sandy White/Sandy Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE/CSA/CB/BIS/ERP




Led parameter

Led Brand&Type&CCT	OSRAM COB
CRI	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	80~85Lm/W
Led chip numbers	1PCS
Lumen	3000K: 583.03Lm 4000K: 598.71Lm 5000K: 605.52Lm



Driver parameter

Driver	No Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC30-42V 150mA, 7W
Powerrating	≥0.5/≥0.85
Typical Efficiency	≥80%
Certificate	CE, CCC, CB, ENEC, RCM
Ta/Tc,Surge	45℃/75℃,1000V
Driver	Triac Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC27-42V 150mA, 7W
Powerrating	0.9
Typical Efficiency	≥72%
Certificate	CE, ENEC, RCM CB
Ta/Tc,Surge	45℃/75℃,1000V




Packaging parameter

Quantity(pcs/Ctn)	40
N.W.(Kg/Ctn)	9.4
G.W.(Kg/Ctn)	12.1
Inner Box(mm)	L95*W95*H120
Outer Box(CM)	L50*W21*H50
Volume(M³/Ctn)	0.0525
N.W. :(g/PC)	270
N.W. :(g/PC)	235

ALTH0770A-11W


Basic parameter

Warranty	5 years
Wattage	11W
Size(mm)	Φ110*H115
Cutout	Φ95
Installation	embedded
IP Rating	IP20
Beam Angle	15°23°38°
Fitting Material	Aluminum
Finish Color	Sandy White/Sandy Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE/CSA/CB/BIS/ERP




Led parameter

Led Brand&Type&CCT	OSRAM COB
CRI	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	80~85Lm/W
Led chip numbers	1PCS
Lumen	3000K:889.99Lm 4000K:913.56Lm 5000K:932.52Lm



Driver parameter

Driver	No Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC30-42V 250mA, 11W
Powerrating	0.55/≥0.85
Typical Efficiency	≥83%
Certificate	CE, CCC, CB, ENEC, RCM
Ta/Tc,Surge	45℃/75℃,1000V
Driver	Triac Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC32-48V 250mA, 11W
Powerrating	0.9
Typical Efficiency	≥82%
Certificate	CE, ENEC, RCM CB
Ta/Tc,Surge	45℃/75℃,1000V



Packaging parameter

Quantity(pcs/Ctn)	30
N.W.(Kg/Ctn)	12.39
G.W.(Kg/Ctn)	13.8
Inner Box(mm)	L115*W115*H150
Outer Box(CM)	L60*W36.5*H32.5
Volume(M³/Ctn)	0.071
N.W. :(g/PC)	460
N.W. :(g/PC)	413

