

Specification

ALXS0675A



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Design concept

Classic simple appearance, provide sand black, sand white, sand gold, sand silver and other surface treatment, more suitable for more space. Deep anti-glare design coupled with the selection of high lumen light source, the whole lamp has enough lumen output without glare. The deep anti-glare cover of the product is also made of aluminum material, which makes the texture of the lamp unified.

Range of application


Hotels, supermarkets, office space, home lighting, commercial chains, etc.



ALXS0675A-6W


Basic parameter

Warranty	5 years
Wattage	6W
Size(mm)	Φ55*H85
Cutout	/
Installation	Ceiling surface
IP Rating	IP20
Beam Angle	10°23°36°
Fitting Material	Aluminum
Finish Color	Sandy White/Sandy Black
	Sandy Silver/Sandy Gold
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE/CSA/CB/BIS/ERP




Led parameter

Led Brand&Type&CCT	OSRAM COB
CRI	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	80~90Lm/W
Led chip numbers	1PCS
Lumen	3000K: 500.11Lm
	4000K: 510.96Lm
	5000K: 525.72Lm



Driver parameter

Driver	No Dimming Eaglelise No flicker
Input	AC220-240V 50/60Hz
Output	DC24-42V 150mA,6W
Powerrating	0.5
Typical Efficiency	≥81%
Certificate	ENEC,CCC,CB,CE
Ta/Tc,Surge	45℃/75℃,1000V




Packaging parameter

Quatlity(pcs/Ctn)	50
N.W.(Kg/Ctn)	12.5
G.W.(Kg/Ctn)	13.8
Inner Box(mm)	L60*W60*H105
Outer Box(CM)	L32*W32*H22.5
Volume(M³/Ctn)	0.02304
N.W.:(g/PC)	250
N.W.:(g/PC)	220

ALXS0675A-8W


Basic parameter

Warranty	5 years
Wattage	8W
Size(mm)	Φ75*H95
Cutout	/
Installation	Ceiling surface
IP Rating	IP20
Beam Angle	10°23°36°
Fitting Material	Aluminum
Finish Color	Sandy White/Sandy Black
	Sandy Silver/Sandy Gold
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE/CSA/CB/BIS/ERP




Led parameter

Led Brand&Type&CCT	OSRAM COB
CRI	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	80~90Lm/W
Led chip numbers	1PCS
Lumen	3000K:679.15Lm
	4000K:690.95Lm
	5000K:710.01Lm



Driver parameter

Driver	No Dimming Eaglelise No flicker
Input	AC220-240V 50/60Hz
Output	DC24-42V 200mA,8W
Powerrating	0.5
Typical Efficiency	≥81%
Certificate	ENEC,CCC,CB,CE
Ta/Tc,Surge	45℃/75℃,1000V



Packaging parameter

Quantity(pcs/Ctn)	30
N.W.(Kg/Ctn)	12.3
G.W.(Kg/Ctn)	13.6
Inner Box(mm)	L80*W80*H115
Outer Box(CM)	L42*W26*H24.5
Volume(M³/Ctn)	0.026754
N.W.:(g/PC)	410
N.W.:(g/PC)	365

