

Specification

ALTD0291D



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Design concept

As a model of basic lighting, it is often favored by people for its simple but not simple shape in the field of lighting application. Famous and excellent lighting LTD0291 series products are suitable in size and excellent in light efficiency. They are the first choice for home and business.

Range of application


Hotels, supermarkets, office space, home lighting, commercial chains, etc.



LTD0291D-15WY


Basic parameter

Warranty	5 years
Wattage	15W
Size(mm)	Φ175*H52mm
Cutout	/
Installation	Surface Mounted
IP Rating	IP20
Beam Angle	120°
Fitting Material	Aluminum
Finish Color	Sand White / Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE,CSA,CB,BIS,ERP




Led parameter

Led Brand&Type&CCT	Everlight SMD 2835
CRI	≥80 ≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	85~95Lm/W
Led chip numbers	12B12C - 144PCS
Lumen	3000K: 1296.16Lm 4000K: 1371.22Lm 5000K: 1420.72Lm



Driver parameter

Driver	No Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC22-40V 350mA, 15W
Powerrating	0.55
Typical Efficiency	≥83%
Certificate	ENEC CE CCC CB ERP RCM
Ta/Tc,Surge	45℃/75℃,1000V




Packaging parameter

Quatity(pcs/Ctn)	20
N.W.(Kg/Ctn)	12
G.W. (Kg/Ctn)	14.3
Inner Box(mm)	L185*W65*H185
Outer Box(CM)	L39*W35.5*H39
Volume(M³/Ctn)	0.054
N.W. :(g/PC)	684
N.W. :(g/PC)	586

LTD0291D-20WY


Basic parameter

Warranty	5 years
Wattage	20W
Size(mm)	Φ210*H52mm
Cutout	/
Installation	Surface Mounted
IP Rating	IP20
Beam Angle	120°
Fitting Material	Aluminum
Finish Color	Sand White / Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE,CSA,CB,BIS,ERP




Led parameter

Led Brand&Type&CCT	Everlight SMD 2835
CRI	≥80 ≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	85~95Lm/W
Led chip numbers	16B12C - 192PCS
Lumen	3000K:1741.05Lm 4000K: 1806.12Lm 5000K:1836.28Lm



Driver parameter

Driver	No Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC24-42V 500mA, 20W
Powerrating	0.9
Typical Efficiency	≥85%
Certificate	ENEC CE CCC CB ERP RCM
Ta/Tc,Surge	45℃/75℃,1000V



Packaging parameter

Quatity(pcs/Ctn)	16
N.W.(Kg/Ctn)	10.88
G.W. (Kg/Ctn)	13.6
Inner Box(mm)	L220*W65*H220
Outer Box(CM)	L46*W28.5*H46
Volume(M³/Ctn)	0.06
N.W. :(g/PC)	790
N.W. :(g/PC)	673

LTD0291D-30WY


Basic parameter

Warranty	5 years
Wattage	30W
Size(mm)	Φ250*H52mm
Cutout	/
Installation	Surface Mounted
IP Rating	IP20
Beam Angle	120°
Fitting Material	Aluminum
Finish Color	Sand White / Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	CE,CSA,CB,BIS,ERP




Led parameter

Led Brand&Type&CCT	Everlight SMD 2835
CRI	≥80 ≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	85~95Lm/W
Led chip numbers	20B12C - 240PCS
Lumen	3000K: 2394.46Lm 4000K: 2412.15Lm 5000K: 2435.13Lm



Driver parameter

Driver	No Dimming Eaglerise No flicker
Input	AC220-240V 50/60Hz
Output	DC24-42V 700mA, 30W
Powerrating	0.95
Typical Efficiency	≥87%
Certificate	ENEC CE CCC CB ERP RCM
Ta/Tc,Surge	45℃/75℃,1000V



Packaging parameter

Quatity(pcs/Ctn)	10
N.W.(Kg/Ctn)	9.25
G.W. (Kg/Ctn)	11.1
Inner Box(mm)	L260*W65*H260
Outer Box(CM)	L54*W35.5*H27.5
Volume(M³/Ctn)	0.0527
N.W. :(g/PC)	1067
N.W. :(g/PC)	924